FARADAY
TECHNOLOGY, INC.

Multiphysics Modeling Prediction of Electrochemically Machined Through-Hole Geometries

AiMES 2018

Cancún, MX

2 Oct 2018

Brian Skinn^a, Timothy Hall^a, Stephen Snyder^a,
K.P. Rajurkar^b, E.J. Taylor^a

^a Faraday Technology, Inc., Englewood, OH 45315

^b Dept. of Mechanical & Materials Engineering, University of Nebraska – Lincoln,
Lincoln, NE 68588

BrianSkinn@FaradayTechnology.com

Electrochemical Machining

Electrochemical Machining

Key advantages[†]:

- Applicability to difficult to cut materials,
 - No tool wear/No (thermal/mechanical) surface damage,
- High material removal rate,
- Smooth bright surface finish, and
- Production of parts with complex geometry.

Key challenges[†]:

1. Disposal of machining products ← (prior Faraday)
2. Electrolyte processing ← (prior Faraday)
3. Tool design ← (current Faraday)
4. Machining accuracy ← (current Faraday)
5. Process monitoring ← (prior sensor/automation advancements)

[†]K.P. Rajurkar, D. Zhu, J.A. McGeough, J. Kozak, A. De Silva, "New Developments in Electro-Chemical Machining" *Annals of the CIRP* Vol 82(2) 1999.

Target ECM Application: Integrated Muzzle Brakes

Modular Brake

(from patent literature)

Cler, D.L. and D. Forliti. U.S. Patent No. 7,600,461, issued 13 Oct 2009

Integrated Brake

(simplified proof-of-concept model)

Target ECM Application: Integrated Muzzle Brakes

Modular Brake

(from patent literature)

Cler, D.L. and D. Forliti. U.S. Patent No. 7,600,461, issued 13 Oct 2009

Integrated Brake

(simplified proof-of-concept model)

Target ECM Application: Development Strategy

FARADAY TECHNOLOGY, INC.

COMSOL Modeling

Relevant Physical Phenomena

**Diffusion
Convection**

Electric Field

**Fluid
Mechanics**

**(Electro)chemical
Reactions**

**Ohmic & Viscous
Heating**

F. Klocke, M. Zeis, S. Harst, A. Klink, D. Veselovac, M. Baumgartner “Modeling and Simulation of the Electrochemical Machining Material Removal Process for the Manufacture of Aero Engine Components” *Procedia CIRP* 8 265-270 (2013).

Simulated Physical Phenomena

ECM Tool/Flow Configurations

Electric Field – Tube vs Rod Tool

**Flow-Through
Tube Tool**

**Cross-Flow
Rod Tool**

Part Current Density Distribution – Rod vs Tube

2V Applied Potential — 100 mS/cm Electrolyte Conductivity — 0.0945" Inter-Electrode Gap

Tool Shape Effect on Machined Profile

- Time-dependent simulations WITH geometry deformation
- 2 V applied potential
100 mS/cm electrolyte conductivity
0.0945" initial inter-electrode gap
0.00044"/min tool movement rate
 $\frac{1}{32}$ " walls for tube tools

Machining Fidelity – Inter-Electrode Gap

0.100" Gap

0.005" Gap

FARADAY TECHNOLOGY, INC.

ECM Tests

ECM Apparatus

Rod or Tube Tool

3-D Printed Flow Module

4130 Steel Flat Panel ECM Part

ECM Experimental Parameters

Modeling – Rod/Tube Tool Tests

Cross-Flow
Rod Tool

Flow-Through
Tube Tool

Modeling – ECM Test Matrix – Rod/NaCl

Rod Tool – NaCl – 10 V_{DC} – $0.006''\text{ min}^{-1}$ – $0.075''$ Initial Gap – 20 min Duration

Modeling – ECM Test Matrix – Tube/NaCl

Tube Tool – NaCl – 10 V_{DC} – $0.006''\text{ min}^{-1}$ – $0.075''$ Initial Gap – 20 min Duration

Summary

- GOAL: Multiphysics modeling for rapid, accurate ECM tool design to obtain complex part shapes
Reduce/eliminate multiple prototyping steps
- Preliminary modeling of core physics
 - Primary current distribution
 - Geometry deformation
- Small inter-electrode gap critical
- Additional physics likely needed for accurate simulations
 - *Subsequent modeling to include flow, surface reaction/polarization effects, etc.*

Acknowledgment

- This material is based upon work/resources supported by:
 - Commercial Partners
 - SBIR/STTR Grants
 - US Army (*synergistic activities*)
 - Faraday Corporate
- Contact Information:
Brian T. Skinn
Ph: +1 937 836 7749
Email: BrianSkinn@FaradayTechnology.com

Thank You!